

# **Bison Barrier**

Specification Sheet WFS150000

06/02/24




#### **Bison Barrier**

The Bison Barrier is a water filled unit for delineation of traffic around sites. Weighing 400kg when full, the barrier can withstand wind speeds of up to 75mph.

Solid hoarding or a mesh fence panel can be added for additional safety and security. This can be personalised if required.

With the addition of a mesh or solid panel, the Bison Barrier has an overall height of 2m and can take standard pedestrian or vehicle gates.




**Bison Barrier with Mesh** 



Bison Barriers with Hoarding and infill panels

# **Key Features**

- > Chapter 8 reflective strip
- > Can be used with solid hoarding, or mesh fence panels
- > Can be used with vehicle and pedestrian gates
- > Can rotate 90° degrees
- > Fill capacity 400 litres
- > 100% recyclable



#### **Bison Specification**

Description	Size (mm)	Weight (kg)	Weight Filled (kg)
WFS150000 - Bison Barrier	H1000 x W2000 x D400	35	400
WFS150020 - Bison Std/800 Anti-Climb Mesh Panel	H1050 x W1938 x D38	8	_
WFS150025 - Bison Std/800 2in Heavy Duty Mesh Panel	H1050 x W1938 x D38	9	_
WFS150030 - Bison Std/800 Hoarding Panel	H1050 x W1938 x D38	17.5	_
WFS150060 - Bison Std/800 Hoarding Infill Panel	H960 x W140 x D1.2	1	_

5

1 Bison Barrier Single Unit



**58** mph

Wind speed withstood, not to

failure point.

Wind speed withstood, not to failure point.







### **Wind Resistance**

The Bison Barrier has been rigorously tested within the MIRA wind tunnel, and achieved multiple Class A passes.

The solid, water-filled nature of the Bison barrier provides the perfect based for the mesh and hoarding panels. Use the barriers alone for an 'A Class' wind resistance performance.

Please see to the right the MIRA Class passes and wind resistance speeds achieved for each of the panels displayed.

2 Bison Barrier + Mesh Fence Panel





3 Bison Barrier + Hoarding Panel



38 mph

Wind speed withstood, not to failure point.




# 90° degree layout

The Bison is an versatile barrier can be easily positioned at 90° angles.

No additional accessories, adaption barriers or brackets are required to enable the barrier to create corners.

The barrier simply rotates to the angle required using the interlocking arm.



Easily create 90° degree angles



**Bison barriers forming curve** 



Bison barrier end pin




90° angle





## **Technical Details**

**Standard Fencing Panel** 



#### **Alternative Options**










## **Technical Details**

Fencing with Gates



# Installation parts Bison Water Filled Barrier - Measurements in mm

**Standard parts:** Please see below pictures and quantities of additional parts you will receive with each Bison Barrier, the parts below are an essential safety requirement when installing the Bison correctly.

Drainage plug
Quantity: 1



Size (mm)	Weight (kg)
H65 x W65 x D28	-

2 Filler cap
Quantity: 1



Size (mm)	Weight (kg)
H20 x W100 x D100	-

Accessory parts: The following accessories are required when attaching fence or hoarding panels to the bison barriers (both the standard and 800 model). Additional items (such as adaption flags) will be required should you require gates. Please contact our sales team for more information.

1 M10 x 50mm Hex head bolts Quantity: 4



Size (mm)	Weight (kg)
W17 x D50	-

M10 x 50 x 1.5mm flat washers Quantity: 4



Size (mm)	Weight (kg)
W50 x D1.5	-

3 Couplers
Quantity: 2



Size (mm)	Weight (kg)
H50 x W52 x D130	0.2

4 Fence or Hoarding panels
Quantity: 1 per barrier



Size (mm)	Weight (kg)
H1050 x W1938 x D38	17

5 Hoarding Infill Panel
Quantity: 1 per barrier if
required



Size (mm)	Weight (kg)
H960 x W140 x D15	1