



15/10 Safe Cover

SPECIFICATION SHEET



15/10 Safe Cover



The 15/10 Safe Cover is suitable for 3.5 tonnes vehicles over a 900mm trench and uses patented flexi-edge technology.

The patented Flexi-Edge technology makes the 15/10 Safe Cover anti-slide. It is moulded around the anti-slide technology, on the underside & edges of the Safe Cover unit.

The Infill Strip completes the Safe Cover system, used to connect several trench covers in a line to prevent drifting. The Infill Strip also has the added benefit of removing trip hazards between Safe Covers.

Key Features

- Designed with National Grid
- Complies with HAUC's 2018/01 Advice Note
- LowPro® edges grip the asphalt, pinning not required in most applications
- Suitable for 3.5T vehicles over a 900mm trench & pedestrians over a 1200mm trench
- Enquire about minimum order quantities for customisations
- Use with LowPro® Infill to remove trip-hazards
- Designed & manufactured in the UK
- Fitted with gas vents & probe hole
- Moulded anti-slip surface
- 100% recyclable
- Shock resistant

Weight 38kg



15/10 Safe Cover Specification

Length*	Width	Height	Weight
1500mm	1000mm	37mm	38kg

Length end to end*

15/10 Long Infill Specification

Length	Width	Height	Weight
1500mm	150mm	35mm	2.3kg

15/10 Short Infill Specification

Length	Width	Height	Weight
1500mm	150mm	35mm	2kg

15/10 Safe Cover Unit



Infill Strips

